

# HGA RACK 2U PRO (SX 3080)

PEM Rack 19 inch Hydrogen generator  
with ZeroAir integrated

The HydroGen series **HGA RACK 19" 2U PRO** is able to generate up to 600 cc/min Hydrogen with purity better than 99.99999% and pressure up to 16 bar (232 PSI). An AirGen output can deliver hydrocarbon free pure Air with a flow up to 2000 cc/min. The **HGA RACK 19 inch 2U PRO** includes an electrolytic cell with polymeric membrane (PEM) using distilled water. The two-column PSA drying system with automatic regeneration ensures the maximum grade of hydrogen purity, and is completely maintenance-free.

The **HGA RACK 19 inch 2U PRO** is the ideal Hydrogen and Air Generator for all GC-FID detectors. The on-board CPU constantly controls the operating parameters to guarantee full safety. The touch-screen LCD interface provides simple and user-friendly management of all functions on the unit.

## Main Applications

- Carrier gas for GC and GC-MS
- GC-FID / GC-NPD / GC-FPD
- THA

## Main Advantages

- ✓ Quick installation
- ✓ Easy use
- ✓ Hydrogen flow rate up to 600 cc/min
- ✓ ZeroAir flow rate up to 2000 cc/min
- ✓ Pressure up to 16 bar (232 psi)
- ✓ Hydrogen purity: 99.99999%
- ✓ THC: < 0.1 ppm
- ✓ RS 485 and USB as standard
- ✓ LAN optional
- ✓ Dryer with no maintenance
- ✓ Reduced foot print: 19 inch rack 2U
- ✓ High pressure GLS electronically controlled (patented)





## Specifications

Models: HGA 2U PRO	100	160	250	350	600
<b>General data</b>					
Electrolytic cell	PEM technology				
Drying system	PSA (Pressure Swing Adsorption)				
H2 purity	>99.99999% *1				
Outlet pressure	12 bars (174 psi) / 16 bars (232 psi) (optional)				
H2 flow-rate cc/min (Max)	100	160	250	350	600
Dimensions	Standard 19 inch 2U RACK (48 cm deep)				
Net weight (no water in tank)	18 kg				
<b>Communication</b>					
RS485/USB	Standard				
LAN	Optional				
<b>Software functions</b>					
Parallel mode	Ready on board				
Automatic tank refill	Standard				
<b>Water</b>					
Quality	Deionized, ASTM II, <0.1uS				
Supply pressure (min, Max)	0 bars (0 psi), 0.5 bar (7.25 psi)				
Internal tank capacity	0.3 l				
<b>Electrical data</b>					
Type of connection	IEC 320-C14				
Power supply voltage	100-240 Vac (±10%) 50/60 Hz				
Nominal power (Max)	350W				500W
Fuse rating (5x20 mm)	4A (250VAC – T)				
<b>Connections</b>					
Hydrogen outlet	1/8" compression fitting				
Water (inlet, drain)	Quick release push-in fitting				
<b>ZeroAir section</b>					
Inlet pressure (Max)	8 bars (116 psi)				
THC (Inlet Air)	100ppm				
Outlet flow rate (Max)	2000 cc/min				
Outlet pressure (Max)	Inlet pressure – 0.5 bars (8 psi) at maximum flow				
THC (ZeroAir Outlet)	<0.1ppm				
Inlet port	1/8" BSPP female				
Outlet port	1/8" BSPP female				

\*1 Referred to O<sub>2</sub> - DewPoint < -75°C (< -103°F), Atmospheric Dew point (ADP)

### Ordering codes

#### Gas Generators

6920.17.010	HGA 2U PRO 100
6920.17.016	HGA 2U PRO 160
6920.17.025	HGA 2U PRO 250
6920.17.035	HGA 2U PRO 350
6920.17.060	HGA 2U PRO 600

#### Consumable

6930.00.091	Deionizer water filter
6930.00.017	Filter elements for ZA RACK series / HGA 2U series / HGA ST series



**LNI Swissgas**

www.lni-swissgas.eu

LNI Swissgas Srl

Registered office: Via Sassoferrato 1, 20135 Milano MI

Logistics centre: Via E. Mattei 9, 35038 Torreglia PD