

Model 2020 Portable Zero Air Source

Overview

The Model 2020 is a portable source for clean, dry air designed to meet a wide range of requirements for the environmental industry. From supplying air for calibration systems to purge air for permeation ovens, the small package size and weight make the Model 2020 the preferred choice for field and audit personnel as well as operating environments with limited bench space.

The Model 2020 uses an internal permeation drying system for moisture removal and is coupled with filter canisters for scrubbing NO, NO₂, O₃, SO₂ and H₂S. Optional features such as the internal carbon monoxide (CO) oxidizer or external hydrocarbon (HC) oxidizer further the Model 2020's clean air capabilities.

User Benefits

Simple straight-forward controls allow local operation from the front panel, with the option to set the purge frequency and duration for optimum performance. Additionally, the unit automatically drains moisture and pressurized air once powered down. Remote activation is achieved using the air source control port and cable in conjunction with any Sabio calibrator. This exclusive feature allows the user to start and stop the unit as needed to avoid unnecessary run times; increasing pump life and decreasing service intervals.

Standard Features

- ▶ Standard 10 LPM @ 20 PSIG
- ▶ Condensate/purge valving for moisture removal
- ▶ Automatic purge frequencies
- ▶ Front panel mounted pressure gauge
- ▶ Front panel mounted adjustable pressure regulator
- ▶ Front panel mounted purge switch
- ▶ Internal permeation dryer
- ▶ Media canisters for removal of NO, NO₂, O₃, SO₂, H₂S
- ▶ Side mounted carrying strap

Optional Features

- ▶ Tilt-up front handle with tilt-up front feet
- ▶ High-impact transport case
- ▶ Model 2050 HC Catalytic Oxidizer
(separate portable chassis)
- ▶ Dew Point Indicator



SPECIFICATIONS

Specifications subject to change without notice

AIR QUALITY

Standard unit	NO, NO ₂ , O ₃ , SO ₂ , H ₂ S <0.5 ppb
Standard unit w/ CO w/Catalytic Oxidizer	NO, NO ₂ , O ₃ , SO ₂ , H ₂ S <0.5 ppb, CO < 5 ppb
Standard unit with external HC catalytic oxidizer	NO, NO ₂ , O ₃ , SO ₂ , H ₂ S <0.5 ppb, Hydrocarbon ≤ .20 ppb

MECHANICAL

Height	6.5 in. (16.5 cm)
Width	13.9 in. (35.3 cm)
Depth	15.0 in. (38.1 cm)
Average Weight	23 lbs (10.4 kg)

ELECTRICAL

Standard	98-132 VAC
Optional	196-264 VAC, 50/60 Hz