NG CASTORE DT

Membrane Nitrogen generator pneumatic controlled

The NitroGen series **NG CASTORE DT** are Membrane Nitrogen Generators. They are engineered to transform standard compressed air into a safe, regulated supply of Nitrogen with a purity up to 99.5%.

The NG CASTORE DT has been developed to meet specific requirements in terms of gas, flow, purity and pressure in LC-MS applications. It can be also used for the evaporation of solvents in samples being analysed.

Main applications

- LCMS
- Solvent evaporation

Main advantages

- ✓ Compatible with all LCMS
- ✓ Nitrogen purity up to 99.5%
- ✓ Low noise
- ✓ Low maintenance
- Generates nitrogen on demand
- ✔ Designed to run 24 hours a day







Specifications



Models: NG CASTORE DT	10	35
N2 outlet		
Flow rate (Max)	10 l/min	35 l/min
Outlet pressure (Max)	Inlet pressure – 0.5bar (7.2 psi)	
Nitrogen purity Inlet Pressure > 8 bar (116 psi)	> 96% @ 10 l/min	> 95% @ 35 l/min
	> 98% @ 5 l/min	> 98% @ 15 l/min
illet Pressure > 8 bar (116 psi)	> 99.5% @ 3 l/min	> 99.5% @ 9 l/min
Dew point *1	<-60°C (-76°F)	
Air inlet		
Air inlet requirement	ISO8573 – 1:2010 Class [1.4.1]	
Flow rate (Max)	30 l/min	105 l/min
Supply pressure (min; Max)	5 bars (72.5 psi); 10bars (145 psi)	
Temperature (min; Max)	1°C (34°F); 45°C (113°F)	
General data		
Net weight	< 25 kg	
Dimensions (W x D x H)	36 x 67 *2 x 15 cm	
Connections		
N2 outlet	1/4" BSPP female (1/8" BSPP female with outlet filter)	
Inlet	1/4" BSPP female	
Operating/storage conditions		
Temperature	5-35°C (41-95°F)	
Humidity (max, non condensing)	80% [5-35°C (41-95°F)]	
Noise	No noise (no mechanical moving parts)	
IP rating	IP20	
Pollution degree rating	2 (with no aromatic compounds)	
Altitude	< 2000m	

^{*1} Atmospheric Dew Point (ADP)

^{*2} D= 75 cm with external filters

Ordering codes
Gas Generators

6920.51.110 CASTORE DT 10 6920.51.135 CASTORE DT 35

Consumable

6930.00.149 Filter elements for CASTORE DT

